

RoHS compliant

REVISION DATA

SYM	ECN	DESCRIPTION	DATE	APPROVED

NOTES:

Current Rating:1.5AMP

Contact Resistance:20mΩ max

Withstand Voltage:500V AC/DC

Insulation Resistance:1000MΩ min

Operation Temperature:-40℃ to +105℃

Contact Material:Brass

Contact plating:Au or Sn Over Ni

Insulator Material:PA6T+30%GF(UL94V-0)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

HOW TO ORDER

EE - XX P XX - X - X

Total Pins

10 30
14 34
16 40
20 44
24 50
26 60

Insulator Color:

K:Black
U:Blue
W:White

Package Type:

A:Tray
B:Tube
C:W/Cap in Tube
D:W/o Cap in Tape & Reel
E:W/Film in Tube
F:W/Film in Tape & Reel
R:With Cap in Tape & Reel

Plating Code

Full Gold Type	Selective Plated Type Gold Plated on Contact Area Tin Plated on Solder Area	Full Tin Type
00 : Gold Flash 01 : Gold 3u" 02 : Gold 5u" 03 : Gold 10u" 04 : Gold 15u" 05 : Gold 20u" 06 : Gold 30u"	S0: Gold Flash, Tin 100u" S1 : Gold 3u", Tin 100u" S2 : Gold 5u", Tin 100u" S3 : Gold 10u", Tin 100u" S4 : Gold 15u", Tin 100u" S5 : Gold 20u", Tin 100u" S6 : Gold 30u", Tin 100u"	T1 : Tin 100u" T2 : Tin 200u" T3 : Tin 150u"

conectonic



TOLERANCE: ANGLE ±3° X.XXX ±0.15 X.XX ±0.25 X.X ±0.40 X. ±0.50	PROJECTON DATE DRAWN CHECKED APPROVED	 05-06-08' JXL	TITLE: 2.00mm Box Header SMT Type H=5.7mm PART NO: EE-XXPXX-X-X REV: UNIT: SCALE: SIZE:
			A mm 2:1 A4