

N-Channel Enhancement Mode Power MOSFET


PWQ5639DQ6

Features


- Low On Resistance
- Low Gate Charge
- Fast Switching Characteristic

BV _{DSS}	30V
I _D @V _{GS} =4.5V, T _A =25°C	5A
R _{DS(ON)} typ. @ V _{GS} =4.5V, I _D =5A	24mΩ
R _{DS(ON)} typ. @ V _{GS} =2.5V, I _D =4A	28mΩ

Equivalent Circuit



Outline



Ordering Information

Device	Package	Shipping
PWQ5639DQ6	SOT-23 (Pb-free lead plating and halogen-free package)	3000 pcs / Tape & Reel

Absolute Maximum Ratings (T_A=25°C)

Parameter		Symbol	Limits	Unit
Drain-Source Voltage		V _{DS}	30	V
Gate-Source Voltage		V _{GS}	±12	
Continuous Drain Current @ V _{GS} =4.5V, T _A =25°C	*a	I _D	5	A
Continuous Drain Current @ V _{GS} =4.5V, T _A =70°C	*a		4	
Pulsed Drain Current	*b	I _{DM}	20	
Continuous Body Diode Forward Current @ T _A =25°C	*a	I _S	1	
Avalanche Current @ L=0.1mH		I _{AS}	12	
Avalanche Energy @ L=0.5mH		E _{AS}	9	mJ
Total Power Dissipation	T _A =25°C	P _D	1.4	W
	T _A =70°C		0.8	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	-55~+150	°C

Thermal Data

Parameter		Symbol	Steady State	Unit
Thermal Resistance, Junction-to-ambient	*a	R _{θJA}	90	°C/W

Note:

*a. The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2 oz. copper, in a still air environment with T_A=25°C. The power dissipation P_D is based on R_{θJA} and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

*b. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and low duty cycles to keep initial T_J=25°C.

Electrical Characteristics (T_A=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	30	-	-	V	V _{GS} =0V, I _D =250μA
V _{GS(th)}	0.5	-	1.5		V _{DS} =V _{GS} , I _D =250μA
G _{FS}	-	6.7	-	S	V _{DS} =10V, I _D =3A
I _{GSS}	-	-	±100	nA	V _{GS} =±12V, V _{DS} =0V
I _{DSS}	-	-	1	μA	V _{DS} =24V, V _{GS} =0V
R _{DS(ON)}	-	24	32	mΩ	V _{GS} =4.5V, I _D =5A
	-	28	37		V _{GS} =2.5V, I _D =4A
Dynamic					
C _{iss}	-	640	-	pF	V _{DS} =15V, V _{GS} =0V, f=1MHz
C _{oss}	-	65	-		
C _{rss}	-	55	-		
R _g	-	4.2	-	Ω	f=1MHz
Q _g *1, 2	-	8	-	nC	V _{DS} =15V, I _D =5A, V _{GS} =4.5V
Q _{gs} *1, 2	-	1.4	-		
Q _{gd} *1, 2	-	1.8	-		
t _{d(ON)} *1, 2	-	4.4	-	ns	V _{DS} =15V, I _D =5A, V _{GS} =4.5V, R _{GS} =3Ω
t _r *1, 2	-	14	-		
t _{d(OFF)} *1, 2	-	37	-		
t _f *1, 2	-	4.4	-		
Source-Drain Diode					
V _{SD} *1	-	0.75	1.2	V	I _S =1A, V _{GS} =0V
t _{rr}	-	7.8	-	ns	I _F =5A, dI _F /dt=100A/μs
Q _{rr}	-	3.9	-	nC	


Note:

*1. Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%


*2. Independent of operating temperature

Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Body Diode Current vs Source-Drain Voltage




Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature






Typical Characteristics (Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature




Typical Characteristics (Cont.)


Single Pulse Power Rating, Junction to Ambient



Transient Thermal Response Curves




Recommended soldering footprint




Unit:mm

Reel Dimension




Carrier Tape Dimension



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T_{smax} to T_P)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T_{smin})	100°C	150°C
-Temperature Max(T_{smax})	150°C	200°C
-Time(t_{smin} to t_{smax})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T_L)	183°C	217°C
- Time (t_L)	60-150 seconds	60-150 seconds
Peak Temperature(T_P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(t_p)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

SOT-23 Dimension



DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.035	0.049	0.90	1.25	E1	0.047	0.067	1.20	1.70
A1	0.000	0.004	0.00	0.10	E	0.089	0.116	2.25	2.95
A2	0.041	0.045	1.05	1.15	e	0.037 BSC		0.95 BSC	
b	0.012	0.020	0.30	0.50	e1	0.071	0.079	1.80	2.00
c	0.003	0.008	0.08	0.20	L	0.012	0.024	0.30	0.60
D	0.110	0.119	2.80	3.02	θ	0°	8°	0°	8°

Notes: 1.Controlling dimension: millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.